



## 6E1AA

### Marine exhaust - hard wall

### SAE J2006/R2 - ISO 13363/2/A+B

**Tube:** Black synthetic rubber

**Reinforcement:** High tensile textile cords with embedded steel helix wire

**Cover:** Black synthetic rubber - abrasion and ozone resistant

**Use:** Marine wet exhaust. Also suitable for bilge pump connection. Special lightweight construction for maximum flexibility

**Safety factor:** 5:1

**Temperature:** -30 °C +100 °C (-22 °F +212 °F)

| mm  | inch   | mm | inch | bar | psi | mm  | inch  | %   | kg/m  | lb/ft |
|-----|--------|----|------|-----|-----|-----|-------|-----|-------|-------|
| 25  | 1      |    |      | 3   | 45  | 50  | 2,00  | 100 | 0,520 | 0,350 |
| 28  | 1 1/8  |    |      | 3   | 45  | 56  | 2,25  | 100 | 0,570 | 0,385 |
| 32  | 1 1/4  |    |      | 3   | 45  | 64  | 2,50  | 100 | 0,640 | 0,435 |
| 35  | 1 3/8  |    |      | 3   | 45  | 70  | 2,75  | 100 | 0,690 | 0,465 |
| 38  | 1 1/2  |    |      | 3   | 45  | 76  | 3,00  | 100 | 0,750 | 0,505 |
| 40  | 1 9/16 |    |      | 3   | 45  | 80  | 3,00  | 100 | 0,780 | 0,525 |
| 42  | 1 5/8  |    |      | 3   | 45  | 84  | 3,25  | 100 | 0,810 | 0,545 |
| 45  | 1 3/4  |    |      | 3   | 45  | 90  | 3,50  | 100 | 0,870 | 0,585 |
| 48  | 1 7/8  |    |      | 3   | 45  | 96  | 3,75  | 100 | 0,920 | 0,620 |
| 51  | 2      |    |      | 3   | 45  | 102 | 4,00  | 100 | 0,970 | 0,655 |
| 60  | 2 3/8  |    |      | 3   | 45  | 120 | 4,75  | 90  | 1,500 | 1,010 |
| 63  | 2 1/2  |    |      | 3   | 45  | 126 | 5,00  | 90  | 1,570 | 1,060 |
| 70  | 2 3/4  |    |      | 3   | 45  | 140 | 5,50  | 90  | 1,720 | 1,160 |
| 76  | 3      |    |      | 3   | 45  | 152 | 6,00  | 90  | 1,870 | 1,260 |
| 80  | 3 1/8  |    |      | 3   | 45  | 160 | 6,25  | 90  | 1,960 | 1,320 |
| 90  | 3 1/2  |    |      | 3   | 45  | 180 | 7,00  | 90  | 2,380 | 1,600 |
| 102 | 4      |    |      | 3   | 45  | 204 | 8,00  | 90  | 2,680 | 1,805 |
| 115 | 4 1/2  |    |      | 3   | 45  | 230 | 9,00  | 90  | 3,000 | 2,020 |
| 127 | 5      |    |      | 3   | 45  | 254 | 10,00 | 80  | 3,620 | 2,435 |
| 152 | 6      |    |      | 3   | 45  | 304 | 12,00 | 80  | 4,300 | 2,890 |
| 203 | 8      |    |      | 3   | 45  | 406 | 16,00 | 80  | 7,460 | 5,015 |