

// FLEXOR 4SP LT

EN 856 4SP

Tube: oil resistant ultra low temperature synthetic rubber.**Reinforcement:** four high tensile steel spirals.**Cover:** abrasion, ozone and hydrocarbon resistant synthetic rubber.**Application:** very high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water. Specially designed for ultra low temperature applications.**Constant operation:** -55 °C +100 °C (-67 °F +212 °F)**Length:** random

Item Code	↔			↔		↻		↻		⤴		⏪	
	Dash	mm	inch	mm	inch	Mpa	psi	Mpa	psi	mm	inch	kg/m	lb/C ft
1003284	-4	6	1/4	17,9	0,70	45,0	6550	180	26200	150	6,0	0,58	39
1003285	-6	10	3/8	21,4	0,84	44,5	6450	178	25800	180	7,2	0,75	50
1003286	-8	13	1/2	24,6	0,97	42,0	6090	168	24360	230	9,2	0,88	59
1003231	-10	16	5/8	28,2	1,11	35,0	5000	140	20000	250	10,0	1,06	71
1003287	-12	19	3/4	32,2	1,27	38,0	5510	152	22040	300	12,0	1,44	97
1003288	-16	25	1	39,7	1,56	32,0	4640	128	18560	340	13,6	1,96	132

// FLEXOR 4SH LT

EN 856 4SH

Tube: oil resistant ultra low temperature synthetic rubber.**Reinforcement:** four high tensile steel spirals.**Cover:** abrasion, ozone and hydrocarbon resistant synthetic rubber.**Application:** very high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water. Specially designed for ultra low temperature applications.**Constant operation:** -55 °C +100 °C (-67 °F +212 °F)**Length:** random

Item Code	↔			↔		↻		↻		⤴		⏪	
	Dash	mm	inch	mm	inch	Mpa	psi	Mpa	psi	mm	inch	kg/m	lb/C ft
1003232	-16	25	1	38,7	1,52	38	5510	152	22000	340	13,6	1,96	132
1003289	-20	32	1 1/4	45,5	1,79	35	5000	140	20000	460	18,4	2,47	165
1003290	-24	38	1 1/2	53,5	2,11	29	4200	116	16800	560	22,4	3,27	219
1003291	-32	51	2	68,1	2,68	25	3650	100	14500	700	28,0	4,67	313