

// PRESSURE WASH

// ALFAJET 210

Tube: oil, detergents and hot water resistant synthetic rubber.

Reinforcement: one high tensile steel braid.

Cover: Smooth. Abrasion, ozone and hydrocarbon resistant blue synthetic rubber, pin-pricked. Black cover also available.

Application: high pressure power cleaners. Specially designed for hot water applications. **Not recommended for steam service.**

Constant operation: -40 °C +100 °C (-40 °F +212 °F)

Length: random



Item Code	↔			↔		↻		↻		⤴		⚖	
	Dash	mm	inch	mm	inch	Mpa	psi	Mpa	psi	mm	inch	kg/m	lb/C ft
1000192	-4	6	1/4	12,1	0,48	21	3000	84	12000	50	2,0	0,18	12
1000185	-5	8	5/16	14,1	0,56	21	3000	84	12000	60	2,4	0,23	15
1000098	-6	10	3/8	15,6	0,61	21	3000	84	12000	65	2,6	0,28	19
1000166	-8	13	1/2	19,5	0,77	21	3000	84	12000	90	3,6	0,42	28

// ALFAJET 400

Tube: oil, detergents and hot water resistant synthetic rubber.

Reinforcement: two high tensile steel braids.

Cover: Smooth. Abrasion, ozone and hydrocarbon resistant blue synthetic rubber, pin-pricked. Black cover also available.

Application: high pressure power cleaners. specially designed for hot water applications. Not recommended for steam service.

Constant operation: -40 °C +100 °C (-40 °F +212 °F)

Length: random



Item Code	↔			↔		↻		↻		⤴		⚖	
	Dash	mm	inch	mm	inch	Mpa	psi	Mpa	psi	mm	inch	kg/m	lb/C ft
1000221	-4	6	1/4	13,2	0,52	40	5800	160	23200	70	2,8	0,27	18
1000220	-5	8	5/16	14,9	0,59	40	5800	140	20000	76	3,0	0,31	21
1000219	-6	10	3/8	16,7	0,66	40	5800	130	18850	90	3,6	0,36	24
1000218	-8	13	1/2	20,1	0,79	40	5800	120	18000	115	4,6	0,47	32