



## // 230AH

**Sea water 20 bar (300 psi) - Fire resistant  
ISO 15540**

**Tube:** black conductive NBR.

**Reinforcement:** high tensile steel cords.

**Cover:** fiberglass fabric coated with red CSM - abrasion, ozone and hydrocarbon resistant.

**Application:** firewater main systems on board off shore installations and sea going vessels.

Also suitable for fuel and oil. Fire resistant 30 min at +800 °C.

**ABS Type approved hose assemblies.**

**Constant operation:** -30 °C +100 °C (-22 °F +212 °F)

**Note:** steel helix wire and corrugated cover ID ≥ 152 mm

↔		↔		↻		↻		⤴		⚡	📦	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
32,0	1 1/4"	56,00	2,20	20	300	100	1500	224,0	8,82		2,50	1,69
38,0	1 1/2"	62,00	2,44	20	300	100	1500	266,0	10,47		2,80	1,89
51,0	2"	79,00	3,11	20	300	100	1500	357,0	14,06		4,20	2,83
76,0	3"	106,00	4,17	20	300	100	1500	532,0	20,94		6,50	4,37
102,0	4"	132,00	5,20	20	300	100	1500	714,0	28,11		8,40	5,65
127,0	5"	157,00	6,18	20	300	100	1500	889,0	35,00		10,90	7,33
152,0	6"	190,00	7,48	20	300	100	1500	912,0	35,91		18,90	12,71
203,0	8"	243,00	9,57	20	300	100	1500	1218,0	47,95		26,80	18,02